

Classification	Description	Product Name, Code	NET Packing Unit	Appearance	Advantages	Approximate Operating Temperature Range
Penetration / Rust Prevention / Lubrication	<ul style="list-style-type: none"> ●Based on oils containing a powerful penetrant and antirust agent. ●Provide excellent lubrication by penetrating even the tiniest of gaps. ●Effective in dehumidification and rust prevention, thanks to humidity-dispelling water displacement properties. ●Suitable for penetrating lubrication and anti-creaking treatment of rotating/sliding parts, chains, and other parts. ●Suitable for disassembly of machines and equipment and loosening of bolts. ●Suitable for rust prevention and removal for metals. 	Hi Slip <small>Allows up-side-down spraying</small> Code : 571839	480ml × 12	Clear Light Yellow	A general-purpose product. Undiluted liquid types (4L or 18 L) also available.	-10~+70°C
		Lubrico 420 <small>Allows up-side-down spraying</small> Code : 531136	420ml × 20 (10×2)		The use of an organomolybdenum compound additive ensures superior lubricity.	-10~+70°C
		Moly RPS Spray Code : 500333	330ml × 48 (6×8)	Black	The use of a molybdenum disulfide (MoS ₂) additive ensures superior lubricity. Undiluted liquid types (4L) also available.	-10~+150°C
		Sumioil EP Spray <small>Allows up-side-down spraying</small> Code : 522036	420ml × 20	Dark Brown	Contain an extreme pressure agent in a high concentration. Ideal for chains, pins, bearings and sliding parts in construction machines, etc. that are operated under extreme pressures.	-10~+70°C
		Sumitec 68 Spray <small>Allows up-side-down spraying</small> Code : 360636	420ml × 24 (12×2)	White	The use of PTFE and Organomolybdenum compound additives ensures superior lubricity. Suitable for lubrication of precision equipment, etc.	-10~+80°C
		Super HS Oil Code : 542019	500ml × 12	Clear Light Yellow	Based on a special penetrating oil designed with a specific focus on penetration. Supplied in non-spray cans.	-10~+70°C
		High Adherence	<ul style="list-style-type: none"> ●Based on a white lubrication oil containing PTFE, a solid lubricant with an excellent low friction property. ●Produces a lubricating film superior in heat resistance and adherence. ●Suitable for the lubrication of rotating and sliding parts in precision equipment. ●Suitable for the lubrication of ejector pins in injection molding machines. 	Sumicron Spray <small>Allows up-side-down spraying</small> Code : 522236	420ml × 20	White
Pinlub <small>Allows up-side-down spraying</small> Code : 571433	330ml × 48 (6×8)			Yellow White	Contains PTFE. Produces an adherent lubricating film.	-20~+200°C